

# 3M Masking Tape Guide for Specialized Applications and Surfaces

		2214	200	2510	2090	2307	2060	235	2308	225	226*	232	233+	234	249	231	2364	2380	2693	2393	214	213		
Color	Tan	R	R			R			R			R		R	R	R	R	R	R	R	R	R	R	
	Black			R				R			R													
	Green						R						R											
	Silver									R														
	Blue				R																			
Hold to and clean removal from specialty surfaces	Stainless steel	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	
	Anodized aluminum																			R	R		R	
	Alodine aluminum											R	R	R						R				
	Phosphate primer															R	R	R			R			
	Chemlease primer																				R			
	Zinc primer															R	R	R			R			
	Nickel plating																				R			
	Brass																						R	
	Copper																						R	
	Silver/silver plate																						R	
	Polycarbonate plastic				R																			
	EPDM rubber				R				R			R	R	R	R							R		R
	Most powder coated paints	R	R	R		R	R	R	R	R	R	R	R	R		R	R	R	R	R	R	R	R	R
	Silicone															R								
Holding strength to common surfaces i.e. steel, paints	Low	R			R										R						R		R	
	Medium		R	R		R	R	R	R	R						R	R					R		
	High										R	R	R	R				R	R					
Paint line	Good	R	R	R											R								R	
	Better				R	R	R	R	R	R				R			R						R	
	Best										R	R	R			R		R	R	R				
Sunlight/outdoor exposure	Up to 7 days on glass				R																			
	Up to 3 days opaque surface						R		R			R	R	R										
	Up to 30 days opaque surface									R														
	Up to 90 days opaque surface										R													
Increasing temperature performance (30 min. bake)		up to 150°F (66°C)			up to 200°F (93°C)			up to 250°F (121°C)			up to 300°F (149°C)			up to 325°F (163°C)			up to 350°F (177°C)							

"R" is recommended

Darker shaded areas represent products in Class I, II, III

\*Laminate of crepe paper/polyethylene

\*NOTE: The technical information and data provided above is a general guide only and should be considered representative or typical only and should not be used for specification purposes.

**PRODUCT USE:** All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application. **WARRANTY AND LIMITED REMEDY:** 3M warrants 3M masking tapes will meet the applicable specifications at the time 3M ships the product. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to repair or replace the product or refund the purchase price. **LIMITATION OF LIABILITY:** Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Business  
Industrial Adhesives and Tapes Division

Bldg. 21-1W-10  
900 Bush Ave.  
St. Paul, MN 55106  
1-800-362-3550  
www.3M.com/masking

Printed in U.S.A.  
Copyright © 2004 3M  
70-0709-5344-6